
Caracteristici



- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- Galvaniseeritud terasplaadist valmistatud isekandev konstruktsioon, on kaetud struktuurse epoksü-polüestrilise valge RAL9016 katega – standardne. Muu värvidega või roostevaba terasest katted on ka saadaval (soovi korral).
- Suur sisselaskevõre, ei nõua intensiivset hooldust.
- Anodeeritud alumiiniumist väljalaskeavad, aerodünaamilise vormiga, iga külg on reguleeritav (0 kuni 15º).
- Rootormootoriga juhitavad, topeltsisselaskeavaga tsentrifugaalventilaatorid, madal müratase. 5-käiguline selektor.EC mudelid on varustatud väga ökonoomsete ja efektiivsete ventilaatoritega.
- "A" tüüp kütteta, ainult ventileerimiseks.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  • Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  • Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

Specificații


50Hz

Model	(m^3/h)	(m)
TWIN KECG 3000 A	9,8-13,8	
TWIN KM 1500 A	9,8-13,1	
TWIN KM 2000 A	9,8-13,1	
TWIN KM 2500 A	9,8-13,1	
TWIN KM 3000 A	9,8-13,1	
TWIN KECM 1500 A	9,8-13,8	
TWIN KECM 2000 A	9,8-13,8	
TWIN KECM 2500 A	9,8-13,8	
TWIN KECM 3000 A	9,8-13,8	
TWIN KG 1500 A	9,8-13,1	
TWIN KG 2000 A	9,8-13,1	
TWIN KG 2500 A	9,8-13,1	
TWIN KG 3000 A	9,8-13,1	
TWIN KECG 1500 A	9,8-13,8	
TWIN KECG 2000 A	9,8-13,8	
TWIN KECG 2500 A	9,8-13,8	

60Hz

Model	(m^3/h)	(m)
TWIN KECM 1500 A	9,8-13,8	
TWIN KECM 2000 A	9,8-13,8	
TWIN KECM 2500 A	9,8-13,8	
TWIN KECM 3000 A	9,8-13,8	

Dimensiuni



L
1000
1500
2000
2500
3000

